

e-STUDIO™ 2000AC

e-STUDIO™ 2500AC

- > Color Multifunction Printer
- > Up to 25 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready



e-STUDIO™ 2000Ac/2500Ac

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/LED Printing/ Heat Roller Fusing
Display	9" Color WVGA Touch Screen Tilting Display
Copy Speed	20/25 PPM (LT)
First Copy Out	Color: 9.5/9.5 Monochrome: 7.1/7.1
Warm-Up Time	Approx. 21 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	ST-R to LD, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 350 Sheets/Max. 2,900 Sheets
Original Feed	Optional 100-Sheet RADF
Scan Speed & Weights	RADF Scan: Up to 73 IPM (Monochrome or Color), Simplex: 9.3-41.8 lb Bond, Duplex: 13.3-41.8 lb Bond
Max. Original Size	LD
Paper Feed Sizes	Drawer 1: 250 Sheets-ST-R to LD Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to LD Opt. Paper Feed Unit: 550 Sheets-ST-R to LD Opt. 550-Sheet Paper Feed Pedestal-ST-R to LD Opt. 550-Sheet Drawer for PFP -ST-R to LD Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Standard: 250 Sheets-16 lb Bond-90 lb Index Stack Feed Bypass: 100 Sheets-16 lb Bond-110 lb Index Opt. Paper Feed Unit: 550 Sheets-16 lb Bond-90 lb Index Opt. 550-Sheet Paper Feed Pedestal: 16 lb Bond-90 lb Index Opt. 550-Sheet Drawer for PFP: 16 lb Bond-90 lb Index Opt. Envelope Cassette for PFP: 16 lb Bond-1b Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type): 17-28 lb Bond Standard Automatic Duplex Unit: 16 lb Bond-90 lb Index
Paper Weights	
Duplex	25% to 400%
Reproduction Ratio	Max. 67.2K Month (e-STUDIO 2000AC) Max. 84K Month (e-STUDIO 2500AC)
Max Duty Cycle	Approx. 126 lb
Weight	22.6" (W) x 23" (D) x 26.1" (H)
Approx. Dimensions	CMY: 33.6K, BK: 38.4K @ 5%
CMYK Toner Yield	120 Volts, 50/60 Hz, 12 Amps
Power Source	Maximum 1.5kW (120V)
Power Consumption	Intel Atom™ 1.33GHz (Dual-Core)
CPU	4GB
Memory	320GB Self-Encrypting Drive FIPS 140-2 Validated
Hard Disk Drive	

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	20/25 Pages Per Minute (LT)
Print Resolution	600 x 600 dpi (5 bit) 600 x 1,200 dpi (1 bit) PS3 Only
Operating Systems	Windows® Vista, Windows Server® 2008/R2, Windows® 7, 8, 8.1, 10, Windows Server® 2012/R2, Macintosh® (Mac OS x 10.6, 10.7, 10.8, 10.9, 10.10, 10.11), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell®
Printing Protocols	Environments, EtherTalk® for Macintosh Environments
Print Drivers	SMB, LPR/LPD, IPP (Ver.1.1) w/Authentication, AppleTalk PAP or EtherTalk™, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
Interface	Windows® Vista SP2 (32-bit, 64-bit), Windows Server® 2008 SP2 (32-bit, 64-bit), Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8/8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows® 10 (32-bit, 64-bit), Mac OS® X 10.6.8, 10.7.4, 10.8, 10.9, 10.10 RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed), Optional 802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple App Store or Google Play)
Device Management	TopAccess, EFMS 6.2 (e-BRIDGE Fleet Management Software)
Account Control	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



Designs and specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. This is a Class 1 laser product complying with IEC60825-1.

© 2017 Toshiba America Business Solutions, Inc. Electronic Imaging Division
Inv. Code 22299 2000AC/2500AC Spec Sheet 5K PG 7/17

Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408 EAL3+), IEEE2600.1, IEEE802.1X, Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp

Environmental Stds.

* Compliant with IEEE2600.1 in High security mode.
Energy Star (V2.0), EPEAT Gold, Blue Angel Mark (RAL UZ-171, MFD), Canadian ECP, Californian Proposition 65, Nordic Swan, RoHS

Certification

WHQL (Windows 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP

Scan Specifications

Scan Speed	RADF Scan: Up to 73 IPM (Monochrome or Color)
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options		
RADF	MR3031	Meta Scan Enabler GS1010
Platen Cover	KA5005PC	IPsec Enabler GP1080
		Unicode Font Enabler GS1007
Additional Paper Options		
Paper Feed Pedestal	KD1058	Single License GS1080
Paper Feed Unit	MY1047	Five Licenses GS1085
Drawer Module	MY1048	Multi-Station Print Enabler
Envelope Cassette Option	MY1049	Single License GS1090
Large Capacity Feeder	KD1059LT	Five Licenses GS1095
Finishing Options		
Inner Finisher	MJ1042	USB Hub Option GR1270
Saddle-Stitch Finisher	MJ1110	Advanced Scanning (ReRite) GB1280V8
Hole Punch Unit (For MJ1042)	MJ6011	SharePoint Connector GB1440
Hole Punch Unit (For MJ1110)	MJ6105	Exchange Connector GB1450
Bridge Kit	KN5005	Google Docs Connector GB1540
Job Separator	MJ5014	Miscellaneous Options
Connectivity/Security Options		
FAX Unit/2nd Line for FAX Unit	GD1370	Stand STAND5005
Wireless LAN/Bluetooth	GN4020	Accessible Arm KK2550
Bluetooth Keyboard	GR9000	Work Tray KK5005
Accessory Tray	GR1250	Manual Pocket KK5008
Panel 10-Key Option	GR1260	Harness Kit for Coin Controller GQ1280
Card Reader Holder	GR1290	

Corporate Office

9740 Irvine Blvd., Irvine, CA 92618

East Coast

Tel: 949-462-6000
959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

9740 Irvine Blvd., Irvine, CA 92618
Tel: 949-462-6000

Web Site

www.business.toshiba.com